



# VIVISOMA CO.,LIMITED

## IFD3 SPECIFICATION REPORT

Module Specifications		
1	Pixel Pitch	3mm
2	Pixel Configuration	SMD2121
3	Module Resolution	64*64
4	Module Size	192mm*192mm
Cabinet Specifications		
1	Cabinet Size(W*H*D)	576*576mm*75mm
2	Cabinet Resolution	192*192
3	Module Quantity	9pcs
4	Material	Die-Casting Aluminum or steel
Screen Parameters		
1	Brightness	≥2000cd/m <sup>2</sup>
2	Pixel Density	111111dots/m <sup>2</sup>
3	Driving Method	1/32
4	View Angle	Horizontal 140°Vertical 140°
5	Best Viewing Distance	6m-150m
6	Brightness Control	Adjustment 4096Grade/each
7	Fresh requency	3000Hz max
8	Frame Frequency	60--85Hz
9	Input Voltage	AC220V/50Hz or AC110V/60Hz with PSE standard
10	Defects Rate	≤0.00001
11	Power Consumption	Average350W/M <sup>2</sup> Max:700W/M <sup>2</sup>
12	Screen weight	38kg/m <sup>2</sup>
13	MTBF	>10,000hours
14	Life span	≥100,000hours
15	Earth Leakage Current	<3mA
16	IP rate	IP31
17	Temperature-operating	- 20℃~60℃
18	Humidity-operating	10%~95%
19	Controlling system	Nova
20	Operating System	Windows98/me/2000/NT/XP

Alex Liao +86-18025306801 liaoyu@vivisoma.com

*Thank You For Your Business!*