



VIVISOMA CO.,LIMITED

OFD10 SPECIFICATION REPORT

Module Specifications		
1	Pixel Pitch	10mm
2	Pixel Configuration	SMD
3	Module Resolution	32*16
4	Module Size	320mm*160mm
Cabinet Specifications		
1	Cabinet Size(W*H*D)	960*960mm*100mm
2	Cabinet Resolution	96*96
3	Module Quantity	36pcs
4	Material	Steel
Screen Parameters		
1	Brightness	≥7500cd/m ²
2	Pixel Density	10000dots/m ²
3	Driving Method	1/4
4	View Angle	Horizontal 140°Vertical 75°
5	Best Viewing Distance	6m-150m
6	Brightness Control	Adjustment 4096Grade/each
7	Fresh requency	2000Hz max
8	Frame Frequency	60--85Hz
9	Input Voltage	AC240V/220V/50Hz or AC110V/60Hz with PSE standard
10	Defects Rate	≤0.00001
11	Power Consumption	Average350W/M ² Max:700W/M ²
12	Screen weight	55kg/m ²
13	MTBF	>10,000hours
14	Life span	≥100,000hours
15	Earth Leakage Current	<3mA
16	IP rate	IP65
17	Temperature-operating	- 20℃ ~60℃
18	Humidity-operating	10%~95%
19	Controlling system	Nova
20	Operating System	Windows98/me/2000/NT/XP

Alex Liao +86-18025306801 liaoyu@vivisoma.com

Thank You For Your Business!