



VIVISOMA CO.,LIMITED

OR4.81 SPECIFICATION REPORT

Module Specifications		
1	Pixel Pitch	4.81mm
2	Pixel Configuration	SMD2121
3	Module Resolution	52*52
4	Module Size	250mm*250mm
Cabinet Specifications		
1	Cabinet Size(W*H*D)	500*500mm*75mm
2	Cabinet Resolution	104*104
3	Module Quantity	4pcs
4	Material	Die-Casting Aluminum
Screen Parameters		
1	Brightness	≥4500cd/m2
2	Pixel Density	62500dots/m2
3	Driving Method	1/13
4	View Angle	Horizontal 140 °Vertical 140 °
5	Best Viewing Distance	6m-150m
6	Brightness Control	Adjustment 4096Grade/each
7	Fresh requency	4000Hz max
8	Frame Frequency	60--85Hz
9	Input Voltage	AC220V/50Hz or AC110V/60Hz with PSE standard
10	Defects Rate	≤0.00001
11	Power Consumption	Average350W/M2 Max:700W/M2
12	Screen weight	38kg/m2
13	MTBF	>10,000hours
14	Life span	≥100,000hours
15	Earth Leakage Current	<3mA
16	IP rate	IP65
17	Temperature-operating	- 20℃ ~ 60℃
18	Humidity-operating	10% ~ 95%
19	Controlling system	Nova
20	Operating System	Windows98/me/2000/NT/XP

Alex Liao +86-18025306801 liaoyu@vivisoma.com

Thank You For Your Business!